

DM147

Product	Double-Coated Tape
Liner	White PE paper 110gsm
Carrier	Transparent Mylar with thickness of 0.012mm
Adhesive	High performance solvent acrylic, pressure sensitive
Description	This tape has a thin Mylar base with a coating of pure solvent acrylic adhesive, giving it excellent tack, high shear and good temperature resistance high as well as low. Good resistance to UV, chemicals, weather conditions, aging and plasticizers.
Range of application	Paper splicing, electronic plates and membrane switches, stereo-mounting, sign assembly, badge and poster mounting
Application temperature	18°C - 25°C; R.H. 55%±10%

Total Thickness	0.077mm – 0.087mm		
Coating Thickness (Side A/B)	0.030mm – 0.040mm		
Temperature resistance	-30°C - 160°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 5 cm		
Holding Power (Side A/B) (PSTC-7)	> 24 hrs 1kg/2.5cmx2.5cm		
Holding Power for temperature Resistance 60°C (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm		
Adhesion (Side A/B)	g/15mm	OZ/0.6in	N/15mm
(PSTC-1)	>1500	>52.91	>14.6
Solvent resistance	Good		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure maximum adhesive contact.

These tests are considered to be relevant to the product's performance; user shall determine suitability in actual environment.